

# Eiffel Opera Ultimate FE SN series

Multigrade Motor Oils – Fully Synthetic Engine Oil



## Product Data Sheet

### Product Description

Eiffel Opera Ultimate FE SN series are advanced technology engine oils blended in high performance fully synthetic basestocks fortified with precisely balanced additive system, specifically to help deliver high level of performance and outstanding protection during long service intervals. It is suitable for the latest downsized engines equipped with stop & start technologies and hybrid engines requiring an API SN specification, where very high viscosity index oils are preferred to provide longer oil drain intervals in modern engines. It provides maximum protection in engines operating under severe conditions, including high-performance turbo-charged, supercharged gasoline and certain diesel multi-valve fuel injected systems.

### Features & Benefits

- Excellent fuel economy & easy cold starts due to extreme fluidity at low temperatures.
- High resistant oil film even at high engine operating temperatures.
- Advanced additive technology, reduces sludge formation which improves engine cleanliness.
- Excellent oxidation & thermal stability, helps in extending oil drain intervals.
- Outstanding engine protection, helps maintain longer engine life and greater compatibility with engine seals.

### Specifications

**Eiffel Opera Ultimate FE meets or exceeds following International and Builder specifications:**

- API SN, SM, SL, SJ
- ILSAC GF-5
- Ford WSS-M2C945-A/WSS-M2C930-A
- General Motors dexos1

**Eiffel Opera Ultimate FE 5W30 SN also meets or exceeds specifications:** Honda HTO-06 & ACEA A1/B1

### Application

Eiffel Opera Ultimate FE series is suitable for use in following:

- Passenger cars, SUVs, light trucks and vans.
- Suitable for all types of modern vehicles, including high-performance turbo-charged, supercharged gasoline multi-valve fuel injected engines
- Excluded service includes - commercial and racing applications, frequent towing or hauling, extremely dusty or dirty conditions or excessive idling.

### Typical Characteristics

Eiffel Opera Ultimate FE	Test Method	Units	5W-20	5W-30
Density @ 15 °C	ASTM D 4052	gm/cc	0.848	0.848
Viscosity @ 100 °C	ASTM D 445	cSt	8.9	10.4
Viscosity @ 40 °C	ASTM D 445	cSt	49.5	58.65
Viscosity Index	ASTM D 2270	-	161	169
Pour Point	ASTM D 97	°C	-39	-39
Flash Point (COC)	ASTM D 92	°C	215	220
Total Base Number	ASTM D 2896	mg KOH/g	8.0	8.0
Phosphorous	ASTM D 4951	% wt	0.078	0.078
CCS Viscosity	ASTM D 5293	cP	4560 @ -30 °C	4560 @ -30 °C

*The above figures are typical of blends with normal production tolerance and do not constitute a specification.*